

### DO'S AND DONT'S

#### DO'S

Keep system tight at all times when traveling

Keep track clean and free of debris.

Keep tarp clean.

When tightening A-Frames, tension one side no more than 1/2 way before you latch and tighten the other side. Once 2nd side is completely tensioned, return to side you started with and tension the rest of the way.

#### DONT'S

Unlatch system at front without taking tension off of the rear tensioning device, regardless of which front tensioning you have.

Never acid wash the tarp. Wipe the tarp or graphics with solvents.

Don't lubricate the wheels or bearings. They are sealed. Lube will attract dust and dirt causing the bearings to fail prematurely.

Never drive with the rear door crank rolled up in the tail.

Don not use the track as a cargo tie down point.

Do not take tension off of A-frames without the safety pin installed.

Drive with large amounts of snow or ice on top of the system.

### TROUBLESHOOTING

#### ROLLING ACTION BINDS WHEN SYSTEM IS PUSHED

Check track for debris (top and bottom).

Check top guide bearings for damage.

Make sure all push up bows are adjusted appropriately.

Make sure all nuts are tight on bow corners.

Extreme cold will make the tarp rigid and cause system to roll harder.

#### TARP FLAPS EXCESSIVELY DURING TRAVEL

Make sure rear tensioning is tight

Adjust push up bows with pins and brackets on sides.

Adjust set nuts on front over center latches if so equipped.

#### A-FRAME BIND OR CATCH

Grease Front slide plate and channel.

Grease large flat washer behind crank receiver

Make sure safety nut is adjusted to a neutral position.

#### BULKHEAD LEAKS

Tighten front tensioning system.

Adjust set nuts on front over center latches if so equipped.

Tighten adjustment nuts on door locks.

Inspect rubber seal on front of front bow.

Temperature changes cause large amounts of condensation on the inside of the system, giving the appearance that the system is leaking.

Should these trouble shooting tips not work for you, please call and speak with a representative. We will do our best to help you over the phone or schedule you for an appointment for repairs. Your Fastrak II, is warranted for 2 years front to back against defects. Feel free to stop by one of our locations anytime for a free inspections.



**TARPSTOP®**



1.877.999.8277



1.419.873.0548



[WWW.TARPSTOP.COM](http://WWW.TARPSTOP.COM)